

Generate CDISC Define.xml & Define.pdf from Metadata Repository

Rohit Banga


Rohit Banga
Consultant
Business & Decision Life Sciences

+32476868287
rohit.banga@businessdecision.com
Business & Decision Life Sciences
Rue Saint-Lambert 141
Sint Lambertstraat
1200 Brussels
Belgium




DRIVE YOUR PERFORMANCE

Topics

- 
- 1 Introduction
 - 2 Generate Define.xml
 - 3 Conclusion

Topics

- 
- 1 **Introduction**
 - 2 **Generate Define.xml**
 - 3 **Conclusion**

Define.xml (CRT-DDS)

- Describes the content and structure of the included data in a machine readable format
- Based on the CDISC Operational Data Model (ODM) making it vendor neutral & platform independent
- Referenced by FDA in the eCTD (electronic submissions) guidance
- Needed for all electronic submissions

Define.xml

☐ Annotated Case Report Form
 ☐ Reviewer's Guide
 ☐ In- & Exclusion Criteria
 ☐ Datasets
 ☐ Value Level Metadata
 ☐ Computational Algorithms
 ☐ Controlled Terminology

Datasets for Study 1000-0000

Dataset	Description	Class	Structure	Purpose	Keys	Location
SE	Subject Elements	Trial Design	One record per actual element per subject	Tabulation	STUDYID, USUBJID, ETCDD, SESTDTC	se.xpt
SV	Subject Visits	Trial Design	One record per subject per actual visit	Tabulation	STUDYID, USUBJID, VISITNUM	sv.xpt
TA	Trial Arms	Trial Design	One record per planned element per arm	Tabulation	STUDYID, ARMCD, TAETORD, ETCDD	ta.xpt
TE	Trial Elements	Trial Design	One record per element	Tabulation	STUDYID, ETCDD	te.xpt
TI	Trial Inclusion/Exclusion Criteria	Trial Design	One record per I/E criterion	Tabulation	STUDYID, IETESTCD	ti.xpt
TS	Trial Summary	Trial Design	One record per trial summary parameter	Tabulation	STUDYID, TSPARMCD, TSVAL	ts.xpt
TV	Trial Visits	Trial Design	One record per planned visit per arm	Tabulation	STUDYID, VISITNUM, ARMCD	tv.xpt
CO	Comments	Special Purpose	One record per comment per subject	Tabulation	STUDYID, USUBJID, RDOMAIN, IDVARVAL	co.xpt
DM	Demographics	Special Purpose	One record per subject	Tabulation	STUDYID, USUBJID	dm.xpt
CM	Concomitant Medications	Interventions	One record per medication intervention episode per subject	Tabulation	STUDYID, USUBJID, CMTRT, CMSDTC	cm.xpt
EX	Exposure	Interventions	One record per constant dosing interval per subject	Tabulation	STUDYID, USUBJID, EXSTDTC, EXTRT	ex.xpt
ML	Meal Data	Interventions	One record per meal intervention episode per subject	Tabulation	STUDYID, USUBJID, VISITNUM, MLTRT, MLTPNUM	ml.xpt
SU	Substance Use	Interventions	One record per substance type per visit per subject	Tabulation	STUDYID, USUBJID, VISITNUM, SUTRT	su.xpt
AE	Adverse Events	Events	One record per adverse event per subject	Tabulation	STUDYID, USUBJID, AETERM, AESTDTC	ae.xpt
DS	Disposition	Events	One record per disposition status or protocol milestone per subject	Tabulation	STUDYID, USUBJID, DSSTDTC, DSDECOD	ds.xpt
MH	Medical History	Events	One record per medical history event per subject	Tabulation	STUDYID, USUBJID, MHTERM	mh.xpt
DC	Pharmacodynamic Concentrations	Findings	One record per sample characteristic per analysis	Tabulation	STUDYID, USUBJID, DCTESTCD, DCSPEC, VISITNUM, DCDTC	dc.xpt

Human Readable Format
(Define.xml + Stylesheet)

```

<ItemGroupDef OID="AE"
  Name="AE"
  Repeating="yes"
  IsReferenceData="no"
  Purpose="Tabulation"
  def:Label="Adverse Events"
  def:Structure="one record per adverse event per subject"
  def:DomainKeys="STUDYID, USUBJID, AETERM, AESTDTC"
  def:Class="Events"
  def:ArchiveLocationID="Location.AE">
  <ItemRef ItemOID="AE.STUDYID"
    OrderNumber="1"
    Mandatory="yes"
    Role="IDENTIFIER"
    RoleCodeListOID="ROLECODELIST" />
  <ItemRef ItemOID="AE.DOMAIN"
    OrderNumber="2"
    Mandatory="yes"
    Role="IDENTIFIER"
    RoleCodeListOID="ROLECODELIST" />

```

Variable	Label	Type	Controlled Terminology	Origin	Role	Comment
STUDYID	Study Identifier	Char		CRF Page 1	IDENTIFIER	The STUDYID variable has a fixed format: 'XXXX_YYYY', where 'XXXX' indicates the 4-digit compound code and the 'YYYY' the 4-digit study code
DOMAIN	Domain Abbreviation	Char	DOMAIN	Derived	IDENTIFIER	
USUBJID	Unique Subject Identifier	Char		Sponsor Defined	IDENTIFIER	The USUBJID variable has a fixed format: 'XXXX_YYYY_ZZZZ', where 'XXXX' indicates the 4-digit compound code, 'YYYY' the 4-digit study code and 'ZZZZ' the 5-digit patient code
AESQ	Sequence Number	Num		Derived	IDENTIFIER	Sequence number (automatically generated) to ensure uniqueness within a dataset for a subject
AETERM	Reported Term for the Adverse Event	Char		CRF Page 11	TOPIC	
AEDECOD	Dictionary-Derived Term	Char	AEDICT_F	Derived	QUALIFIER	AE term decoded to MEDDRA terminology version 10.1
AEBODSYS	Body System or Organ	Char	AEDICT_F	Derived		AE term decoded to MEDDRA

Define.xml - Metadata

Table Metadata

Dataset Name
Dataset Label
Class
Structure
Purpose
Keys

Variable Metadata

Variable Name
Variable Label
Type
Controlled Terminology
Origin
Role
Comment

Value Level Metadata

Source Variable
Value
Label
Type
Controlled Terminology
Origin
Role
Comment

Datasets for Study 1000-0000

Dataset	Description	Class	Structure	Purpose	Keys	Location
AE	Adverse Events	Events	One record per adverse event per subject	Tabulation	STUDYID, USUBJID, AETERM, AESTDTC	ae.xpt

Controlled Terminology

Code Value
Code Text

Computational Algorithms

Reference Name
Computaion Method

Define.xml - Metadata

Table Metadata

Dataset Name
Dataset Label
Class
Structure
Purpose
Keys

Variable Metadata

Variable Name
Variable Label
Type
Controlled Terminology
Origin
Role
Comment

Value Level Metadata

Source Variable
Value
Label
Type
Controlled Terminology
Origin
Role
Comment

Variable	Label	Type	Controlled Terminology	Origin	Role	Comment
STUDYID	Study Identifier	text		Protocol, CRF Page 1	IDENTIFIER	The STUDYID variable has a fixed format: 'XXXX-YYYY', where 'XXXX' indicates the 4-digit compound code and the 'YYYY' the 4-digit study code
DOMAIN	Domain Abbreviation	text	DOMAIN	Assigned	IDENTIFIER	
USUBJID	Unique Subject Identifier	text		Derived	IDENTIFIER	The USUBJID variable has a fixed format: 'XXXX-YYYY-ZZZZ', where 'XXXX' indicates the 4-digit compound code, 'YYYY' the 4-digit study code and 'ZZZZ' the 5-digit patient code

Code Value
Code Text

Reference Name
Computation Method

Define.xml - Metadata

Table Metadata

Dataset Name
Dataset Label
Class
Structure
Purpose
Keys

Variable Metadata

Variable Name
Variable Label
Type
Controlled Terminology
Origin
Role
Comment

Value Level Metadata

Source Variable
Value
Label
Type
Controlled Terminology
Origin
Role
Comment

Value Level Metadata (ValueList.VS.VSTESTCD)							
Source Variable	Value	Label	Type	Controlled Terminology	Origin	Role	Comment
VSTESTCD	BMI	BODY MASS INDEX	text		Derived		See Computational Method: COMPMETHOD.BMI
VSTESTCD	DIABP	DIASTOLIC BLOOD PRESSURE	text		CRF Page 24		
VSTESTCD	HEIGHT	HEIGHT	text		CRF Page 22		
VSTESTCD	PULSE	PULSE RATE	text		CRF Page 24		
VSTESTCD	SYSBP	SYSTOLIC BLOOD PRESSURE	text		CRF Page 24		
VSTESTCD	WEIGHT	WEIGHT	text		CRF Page 22		

Code Value
Code Text

Reference Name
Computaion Method

Define.xml - Metadata

Table Metadata

Dataset Name
Dataset Label
Class
Structure
Purpose
Keys

Variable Metadata

Variable Name
Variable Label
Type
Controlled Terminology
Origin
Role
Comment

Value Level Metadata

Source Variable
Value
Label
Type
Controlled Terminology
Origin
Role
Comment

SEX, Reference Name (SEX)	
Code Value	Code Text
F	FEMALE
M	MALE

Controlled Terminology

Code Value
Code Text

Computational Algorithms

Reference Name
Computaion Method

Define.xml - Metadata

Table Metadata

Dataset Name
Dataset Label
Class
Structure
Purpose
Keys

Variable Metadata

Variable Name
Variable Label
Type
Controlled Terminology
Origin
Role
Comment

Value Level Metadata

Source Variable
Value
Label
Type
Controlled Terminology
Origin
Role
Comment

Computational Algorithms (COMPMETHOD.AGE)

Reference Name	Computation Method
COMPMETHOD.AGE	Equals to (DM.RFSTDTC-DM.BRTHDTC)/365.25

Controlled Terminology

Code Value
Code Text

Computational Algorithms

Reference Name
Computation Method

Define.xml - Metadata

Table Metadata

Dataset Name
Dataset Label
Class
Structure
Purpose
Keys

Variable Metadata

Variable Name
Variable Label
Type
Controlled Terminology
Origin
Role
Comment

Value Level Metadata

Source Variable
Value
Label
Type
Controlled Terminology
Origin
Role
Comment

Controlled Terminology

Code Value
Code Text

Computational Algorithms


Reference Name
Computaion Method

SAS Open Metadata Architecture


- The SAS Open Metadata Architecture is a general-purpose metadata management facility that provides common metadata services to SAS applications.
- The Metadata Architecture consists of :
 - SAS Metadata Server
 - SAS Open Metadata Interface
 - SAS Metadata Model
 - XML transport format and XML representation of metadata



Topics

- 
- 1 Introduction
 - 2 **Generate Define.xml**
 - 3 Conclusion

Metadata Flow



Dataset	Description	Class	Structure	Purpose	Keys
AE	Adverse Events	Events	One record per adverse event per subject	Tabulation	STUDYID, USUBJID, AETERM, AESTDTC
BA	Bleeding Event Assessment	Findings	One record bleeding event assessment per subject	Tabulation	STUDYID, USUBJID, BATESTCD, VISITNUM, BASPID
BE	Bleeding Event	Events	One record per bleeding event per subject	Tabulation	STUDYID, USUBJID, BESPID
BP	Diagnostic Assessments	Findings	One record per test code	Tabulation	STUDYID, USUBJID, BPTESTCD, VISITNUM, BPSPID, BPCAT,
BT	Blood Transfusion	Interventions	One record per blood transfusion per subject	Tabulation	STUDYID, USUBJID, BTTRT, BTSTDTCD, BTSPID
CA	Central Assessments	Findings	One record per assessment per visit per subject	Tabulation	STUDYID, USUBJID, CATESTCD, VISITNUM, CACAT, CASCAT, CALOC, CASPID
CM	Concomitant Medications	Interventions	One record per medication intervention episode per subject	Tabulation	STUDYID, USUBJID, CMTRT, CMSTDTCD, CMCAT, CMINDC
CO	Comments	Special Purpose	One record per comment per subject	Tabulation	STUDYID, USUBJID, ROOMAIN, IDVARVAL
CP	Compliance	Findings	One record per test code	Tabulation	STUDYID, USUBJID, CPTESTCD, VISITNUM
DM	Demographics	Special Purpose	One record per subject	Tabulation	STUDYID, USUBJID
DS	Disposition	Events	One record per disposition status or protocol milestone per subject	Tabulation	STUDYID, USUBJID, DSSTDTCD, EPOCH
EX	Exposure	Interventions	One record per constant dosing interval per subject	Tabulation	STUDYID, USUBJID, EXSTDTCD, EXTRT
HO	Hospitalizations	Events	One record per hospitalisation event per subject	Tabulation	STUDYID, USUBJID, HOTERM
IE	Inclusion/Exclusion Exceptions	Findings	One record per Inclusion/Exclusion criteria exception per subject	Tabulation	STUDYID, USUBJID, IETESTCD
IM	Intake of Investigational Medication	Interventions	One record per intake of investigational medication per subject	Tabulation	STUDYID, USUBJID, IMTRT, IMSPID
LB	Laboratory Test Results	Findings	One record per lab test per time point per visit per subject	Tabulation	STUDYID, USUBJID, LBTESTCD, VISITNUM, LBOTC
MH	Medical History	Events			
RELREC	Related Records	Special Purpose R			
PS	Pharmacokinetic/Pharmacodynamic Sampling	Findings			
SE	Subject Elements	Trial Design			
SR	Surgery	Events			
SU	Substance Use	Interventions			
SUPPAE	Supplemental Qualifiers	Special Purpose R			
SUPPBA	Supplemental Qualifiers	Special Purpose R			
SUPPBE	Supplemental Qualifiers	Special Purpose R			
SUPPBP	Supplemental Qualifiers	Special Purpose R			
SUPPBT	Supplemental Qualifiers	Special Purpose R			
SUPPCA	Supplemental Qualifiers	Special Purpose R			
SUPPDM	Supplemental Qualifiers	Special Purpose R			
SUPPDS	Supplemental Qualifiers	Special Purpose R			
SUPPEX	Supplemental Qualifiers	Special Purpose R			
SUPPIM	Supplemental Qualifiers	Special Purpose R			
SUPPSR	Supplemental Qualifiers	Special Purpose R			
SUPPMH	Supplemental Qualifiers	Special Purpose R			
SV	Subject Visits	Trial Design			
TA	Trial Arms	Trial Design			
TE	Trial Elements	Trial Design			
TI	Trial Inclusion/Exclusion Criteria	Trial Design			
TS	Trial Summary	Trial Design			
TV	Trial Visits	Trial Design			
VS	Vital Signs	Findings			
WA	Wound Assessment	Findings			

Add Metadata

```
%Macro Addtablemetadata( Extension = , Value= , TableId = );
data _null_;
file addmeta;
```

```
PUT '<AddMetadata>';
PUT '<Metadata>';
PUT "<Extension Id  = " &"""""" ;
PUT "      Name = " &""""&Extension"""" ;
PUT "      Value = " &""""&Value"""" ">" ;
PUT '<owningobject>';
PUT " <PhysicalTable objref= " &""""&TableId"""" "/>";
PUT '</owningobject>';
PUT '</Extension>';
PUT '</Metadata>';
PUT '<Reposid>$METAREPOSITORY</Reposid>';
PUT '      <NS>SAS</NS>';
PUT '<!-- OMI_TRUSTED_CLIENT FLAG -->';
PUT '<Flags>268435456</Flags>';
PUT '<Options/>';
PUT '</AddMetadata>';
run;
```

```
Proc Metadata Repos = "&REP_ID." in = addmeta ;
run;
```

```
%Mend Addtablemetadata;
```

- SAS Code to Add Metadata
 - Uses <AddMetadata> method call
 - Uses PROC METADATA

Add Metadata – Results

Basic View Console View

Adverse Events - AE Properties

General Columns Indexes Keys Physical Storage Parameters Notes **Extended Attributes** Advanced

#	Name	Description	Length	Type	Informat
1	STUDYID	Study Identifier	20	Character	(None)
2	DOMAIN	Domain Abbreviation	20	Character	(None)
3	USUBJID	Unique Subject Identifier	20	Character	(None)
4	AESSEQ	Sequence Number	4	Numeric	(None)
5	AESPID	Sponsor ID	4	Numeric	(None)
6	AETERM	Reported Term	200	Character	(None)
7	AEDECOD	Dictionary Code	20	Character	(None)
8	AEBODSYS	Body System	20	Character	(None)
9	AESV	Severity	20	Character	(None)
10	AESR	Seriousness	20	Character	(None)
11	AECN	Action	20	Character	(None)
12	AEREL	Causal Relationship	20	Character	(None)
13	AECUT	Outcome	20	Character	(None)
14	AESCAN	Involved	20	Character	(None)
15	AESCONG	Congestive	20	Character	(None)
16	AESDISAB	Persistent	20	Character	(None)
17	AESDTH	Results	20	Character	(None)
18	AESHOSP	Required	20	Character	(None)
19	AESLIFE	Is Life	20	Character	(None)
20	AESMIE	Other	20	Character	(None)
21	AECONTRT	Concomitant	20	Character	(None)
22	AESTDTC	Start Date	20	Character	(None)
23	AEENDTC	End Date	20	Character	(None)
24	AESTDY	Study Day	20	Character	(None)
25	AEENDY	Study Day	20	Character	(None)
26	AEENRF	End Reason	20	Character	(None)

Extended Attributes for STUDYID

#	Field Name	Value	Description
1	CORE	Req	
2	ORIGIN	Protocol, CRF Page 5	
3	TERM		
4	ROLE	Identifier	

Notes for STUDYID

Notes Assigned:

References

Note text:

The STUDYID variable has a fixed format: 'XXXX-YYYY', where 'XXXX' indicates the 4-digit compound code and the 'YYYY' the 4-digit study code

Documents Assigned:

Name Path

New Delete Attach...

OK Cancel Help

Get Metadata

```
FILENAME INPUT TEMP;
FILENAME OUTPUT "...\\output.xml";
```

```
data _null_;
file Input;
  put '<GetMetadataObjects>';
  put '<Reposid>$METAREPOSITORY</Reposid>';
  put '<Type>PhysicalTable</Type>';
  put '<Objects/>';
  put '<NS>SAS</NS>';
  put '<Flags>388</Flags>';
  put '<Options>';
  put '<XMLSelect search="PhysicalTable[@SASTableName = '@';
  put "" "&NAME" "" ]/TablePackage/SASLibrary[@Libref = " @;
  put "" "&libref" "" @;
  put ']]"/>';
  put '<Templates>';
  put '<PhysicalTable Id="" Name="" Desc="" SASTableName="" >';
  put '<Columns/>';
  put '<Extensions/>';
  put '<Notes/>';
  put '</PhysicalTable>';
  put '<Column ID="" Name="" Desc="" SASColumnLength="" SASColumnType=""';
  put '      SASColumnName="" SASFormat="" SASInformat="">';
  put '      <Extensions/> <Notes/> </Column>';
  put '<Extension ID="" Name="" Desc="" Value=""/>';
  put '<TextStore ID="" Name="" TextType="" StoredText="" />';
  put '</Templates>';
  put '</Options>';
  put '</GetMetadataObjects>;run;
```

```
Proc Metadata Repos = "&Rep_ID." in=input out=results;
run;
```

- SAS Code to Extract Metadata
 - Uses <GetMetadataObjects> method call
 - Uses <XML Select> element to specify search string
 - Uses PROC METADATA


Map XML to SAS Datasets

```
- <GetMetadataObjects>
  <Reposid>A0000001.A5TG5IXN</Reposid>
  <Type>PhysicalTable</Type>
- <Objects>
  - <PhysicalTable Id="A5TG5IXN.AR000001" Name="Adverse Events" Desc="SDTM 3.1.2 Global Standards Table" SASTableName="AE">
    - <Columns>
      - <Column Id="A5TG5IXN.AS000001" Name="STUDYID" Desc="Study Identifier" SASColumnLength="200" SASColumnType="C" SASColumnName="STUDYID"
        SASFormat="" SASInformat="">
        - <Extensions>
          <Extension Id="A5TG5IXN.AN0001G4" Name="CORE" Desc="" Value="Req" />
          <Extension Id="A5TG5IXN.AN0001G5" Name="ORIGIN" Desc="" Value="Protocol, CRF Page 1" />
          <Extension Id="A5TG5IXN.AN0001G6" Name="ROLE" Desc="" Value="Identifier" />
          <Extension Id="A5TG5IXN.AN0001G7" Name="TERM" Desc="" Value="" />
        </Extensions>
        - <Notes>
          <TextStore Id="A5TG5IXN.A900012A" Name="References" TextType="PlainText" StoredText="The STUDYID variable has a fixed format: 'XXXX-
            YYYY', where 'XXXX' indicates the 4-digit compound code and the 'YYYY' the 4-digit study code" />
        </Notes>
      </Column>
      - <Column Id="A5TG5IXN.AS000002" Name="DOMAIN" Desc="Domain Abbreviation" SASColumnLength="200" SASColumnType="C" SASColumnName="DOMAIN"
        SASFormat="" SASInformat="" MetadataCreated="27Aug2009:08:14:00" MetadataUpdated="27Aug2009:08:14:00">
        - <Extensions>
          <Extension Id="A5TG5IXN.AN0001G8" Name="CORE" Desc="" Value="Req" />
          <Extension Id="A5TG5IXN.AN0001G9" Name="ORIGIN" Desc="" Value="Assigned" />
          <Extension Id="A5TG5IXN.AN0001GA" Name="ROLE" Desc="" Value="Identifier" />
          <Extension Id="A5TG5IXN.AN0001GB" Name="TERM" Desc="" Value="DOMAIN" />
        </Extensions>
        - <Notes>
          <TextStore Id="A5TG5IXN.A900012B" Name="References" TextType="PlainText" StoredText="" />
        </Notes>
      </Column>
    - </Columns>
  </PhysicalTable>
- </Objects>
```

- Result of
<GetMetadataObjects>
method call in native
SAS XML Format

Result.xml

Map XML to SAS Datasets



- SAS XML Mapper used to make Map file
- Map file converts Result.xml into SAS Datasets
- Resulting SAS Datasets manipulated to make Define.xml

SAS XML Mapper

Proc Template

```
Proc template;
Define tagset TMP.ComputationMethod;
parent = tagsets.sasxmog;
mvar markup
    OID
    ItemOID;

    define event row;
        start:
        break;
    finish:
        do /if cmp($markup, "FIRST");
            trigger writeFirst;
        done;
        break;
    end;
/* Use SASColumn event to load values into variables*/
define event SASColumn;
    do /if cmp(NAME, "MARKUP");
        set $markup VALUE;
    break;
    done;
    end;
/* Define Tag writing events */
define event writeStart;
    putq "<def:ComputationMethod OID=" $OID ">" CR;
break;
end;

run;
```

- Proc Template program to convert SAS Datasets into Define.xml
- Uses Events to make dynamic templates

[Define.xml](#)

Proc Report

```

ODS PROCLABEL = "Datasets for Study &STUDY_ID.";
PROC REPORT DATA=Table_Metadata nowd noheader nocenter SPLIT=' '
    CONTENTS="SDTM Domains"
    style(report) = [OUTPUTWIDTH = 100%];

columns SASTableName DESCRIPTION CLASS STRUCTURE PURPOSE KEYS XPORT;

define SASTableName/display width=30 "Dataset";
define DESCRIPTION/display width=30 "Description";
define CLASS/display width=10 "Class" ;
define STRUCTURE/display width=40 "Structure";
define PURPOSE/display width=40 "Purpose" ;
define KEYS/display width=30 "Keys" ;
define XPORT/display "Location" ;

COMPUTE XPORT;
URLSTRING = STRIP(XPORT);
CALL DEFINE (_COL_, 'URL', URLSTRING);
ENDCOMP;


RUN;

```

- Proc Report Program to convert SAS Datasets into Define.pdf
- Uses ODS option PROCLABEL, PROC REPORT CONTENTS option to control bookmarks
- Uses COMPUTE block to put Hyperlinks

[Define.pdf](#)

Topics

- 
- 1 Introduction
 - 2 Generate Define.xml
 - 3 **Conclusion**

Conclusion

- Centralized Metadata Repository
- Integrates all the metadata and stores it in one meta model schema that can be accessed easily.
- Compare metadata across several studies which ensure consistency throughout the project.
- Metadata checks can run on this repository to help better quality control.
- Repository can be populated before the actual programming begins



**Thank you
for your attention**

Rohit Banga
Consultant
Business & Decision Life Sciences

+32476868287
rohit.banga@businessdecision.com
Business & Decision Life Sciences
Rue Saint-Lambert 141
Sint Lambertstraat
1200 Brussels
Belgium



DRIVE YOUR PERFORMANCE