

PP11: Common Define.xml File Issues Seen During FDA's JumpStart Service

Peter Glass¹; Caitlin Anderson¹; Margo Cohen¹; Kathryn Matto¹; Austin Taylor¹; Sergiy Sirichenko²; Max Kanevsky²; Michael Beers²; Alan Shapiro³; Barbara Witczak³; Jesse Anderson³; Mary Doi³; Lilliam Rosario³;




¹IBM, ²Pinnacle 21, ³FDA CDER OTS Office of Computational Science

Background


The JumpStart service provides CDER review teams with an assessment of the composition and quality of the clinical trial data submitted within an application. JumpStart provides these data findings to the reviewers within two weeks of the receipt of a new submission, giving reviewers time to clarify issues or make requests of the organizations developing the drug before proceeding in the review process. JumpStart also provides data analyses that highlight areas of concern and may warrant further attention. From inception, the JumpStart service has provided this assessment to over 130 applications. Part of this service is an introduction to and a review of the Define.xml file submitted with study data. The Define.xml file is a critical part of the electronic submission for regulatory review because it defines the metadata structures that should be used to describe the datasets, variables, controlled terminology, and codes. A well-developed and complete data definition file allows the FDA review team to quickly understand the structure of the datasets within the submission and provides a reference that can be used throughout the review cycle. Define.xml file is also an important source of machine-readable metadata, which can be utilized for automated processes. If a Define.xml file has an issue that causes ambiguousness of data or affects the file's usability, it can cause delays to a review team's analysis. The JumpStart team has had the opportunity to work with many Define.xml files from a variety of applicants and has tracked common issues that can occur in the Define.xml file. This poster will highlight some issues that the JumpStart team has encountered during its analysis.

XSL Style Sheet Reference Errors

During the review process, XML files are viewed using different web browsers including Microsoft Internet Explorer. However, with Internet Explorer, in addition to the XML file, XSL files are needed which describe how data in an XML file is to be presented to the user.



A common issue which results in an unusable Define.xml file is using an incorrect stylesheet reference.




Incorrect aCRF Links

One of the most useful functions of the Define.xml file is its ability to link a variable's record in the file to the page where the information was collected in the annotated Case Report Form (aCRF).

Adverse Events (AE) [Location: [ae.xpt](#)]

Variable	Label	Type	Length	Origin
AETERM	Reported Term for the Adverse Event	text	67	CRF Page 3

Example aCRF:



A common issue is an incorrect aCRF link. This may be caused when a file name for an aCRF is changed without updating a reference in Define.xml file. For example, original "blankcrf.pdf" or "acrf-study-1.pdf" renamed to new "acrf.pdf". Another cause can be adding pages to the aCRF without updating links in the Define.xml file.

Limited Detail in Computational Algorithms

Computational algorithms in the Define.xml file allow review teams assess applicant methodology and allow for the verification of derived variables. Algorithms that provide comprehensive detail and are presented in an easy-to-understand format allow for quicker verification and a more thorough understanding of submitted data.

Example of an Algorithm with Limited Detail:

Variable	Label	Derivation/Comment
RFPENDTC	Date/Time of End of Participation	Last date of contact

Example of an Algorithm with Added Detail:

Variable	Label	Derivation/Comment
RFPENDTC	Date/Time of End of Participation	Last known day of contact with subject; If DM.DTHDTC is not NULL then RFPENDTC = DM.DTHDTC. Else RFPENDTC is equal to MAX of --DTC, --STDTC, and --ENDTC variables from all domains.

Computational Algorithms that Reference Internal Datasets

As noted in the issue to the left, CDER review teams depend on clear, reproducible computational algorithms in the Define.xml file to verify the methodology of derived variables. This can be difficult if algorithms contain references to internal applicant datasets or variables which are not submitted in the data package.

Example of an Algorithm with References to Internal Datasets and Variables:

Variable	Label	Derivation/Comment
BRTHDTC	Date/Time of Birth	cat(put(demo.brth_year,4),'-',put(demo.brth_month,z2),'-',put(demo.brth_day,z2))

This algorithm references a dataset (demo) and variables (brth_year, brth_month, brth_day) that cannot be found in any submitted data.

A PhUSE working group is developing a "Define.xml Completion Guide".
http://www.phusewiki.org/wiki/index.php?title=Define_XML_V2.0_Completion_Guidelines_%26_Style_Sheet_Recommendations

Missing or Merged Codelists

Controlled Terminology (CT) tables in the Define.xml file, also known as codelists, help reviewers quickly examine terminology used by applicants and provide a reference for any codes reviewers might encounter during their investigation of study data. Missing codelists can cause errors during validation due to the lack of information to help reviewers understand how data was collected.

